







21.5" HMI Panel PC for Cleanroom - in wall





Slim version 48mm depth







21.5" HMI Panel PC for Cleanroom – in wall



Highlights

HMI PC for in-wall mounting in cleanroom. Save valuable space and service cost without breaking the cleanroom sealing.

Slim version 48 mm for thin cleanroom wall. Very easy to clean and disinfect due to the flat, smooth stainless steel front. Withstands all known cleaning agents and disinfectants.

Cutting-edge touch technology works with gloves improving workflow and productivity. A typical use case would be three layers of gloves, one layer of cotton gloves and two layers of nitrile/latex or silicone gloves. It is also possible to combine with thicker safety gloves. The multi touch display provides auto calibration for seamless operation.

Blue Line's HMIs are designed for 24/7 operation, with a low power consumption, passive cooling and without moving parts for maximum operational reliability.

Available as monitor or with integrated PC. Mounting is possible in walls, machines and control cabinets. Blue Line's modular design makes it possible to configure fully to specific requirements to functionality, finish and environment.

Wall mounted keyboard is optional.

Blue Line's modular design makes it possible to configure to specific needs in functionality, finish and environment. Get free advice from our experts and let us set up a Teams meeting for an online demo and Q&A. Benefit from our experience and knowledge based on numerous installations in biotech and pharmaceutical sites around the world.

- Life Science / GMP / FDA environment
- Cleanroom in-wall integration / panel mount

IT for Demanding Environments



21.5" HMI Panel PC for Cleanroom – in wall

- Slim version available 48 mm depth
- Stainless steel AISI 304 / 316L
- Easy to clean & disinfect

• Withstands all known detergents: iso-propyl alcohol, non-deionized water, VHP, Spor-Klenz™, Klercide, Actisan, LpH®, Vesphene® and more

- Meets all cleanroom, GMP and FDA requirements
- 21.5" PCAP multi touch display
- Can be operated with up to 3 layers of cleanroom gloves
- Full HD resolution 1920 x 1080
- IP65 dust and waterproof
- Integrated PC / client
- Fanless operation
- · Optional Nymi ready integrated reader
- ThinManager support
- Windows 10 / 11 & Linux
- Wide range of options: USB, LAN, serial, reset
- Long product life cycle
- Customisation according to your requirements

Specifications

Model Type

HMI Panel PC for in-wall mounting

Construction

Fully sealed enclosure in stainless steel AISI 304 Optional acid resistant stainless steel AISI 316L

NE

IT for Demanding Environments



21.5" HMI Panel PC for Cleanroom – in wall

On allian				
Cooling				
Fanless				
Ingress Protection				
IP65				
Environment				
Operating temperature		0°C to +50°C		
Storage temperature Humidity		-30°C to +70°C 10 to 90% @ 40°C, non-condensing		
Humidity	10 10 90% 0	20 C, non-condensing		
Certification				
CE / FCC CLASS A				
Display				
21.5"	1920 x 1080, 16:9, FHD	LCD panel		
Touch				
Projected capacitive multi touch (supports gloves)				
Brightness				
300 nits				
Viewing Angle				
178/178				
Processor				
Intel Celeron J6412 4C/4T, 2.0GHz (T	urbo 2.6GHz)			
Chipset				



Integrated SoC RAM Celeron J6412 1 x DDR4 SO-DIMM socket, max 32GB 3200MHz Storage 1 x 2.5" SSD Front Input / Output Option for: USB 2.0 ports COM ports Reset All connectors come with waterproof cap Nymi ready - integrated reader **Rear Input / Output** 1 x Gbe LAN (2 x LAN optional) 1 to 4 x USB 2.0 ports COM ports optional 1 x Power input All connectors come with waterproof cap

Expansion

1 x MiniPCIe slot (internal)

Operating System

Windows 10 / 11 Windows 10 / 11 IoT Enterprise Linux

Thin Client

ThinManager, Microsoft Remote Desktop (RPD), NoTouch OS, VNC, Citrix and others

IT for Demanding Environments





Power Supply

+90V to +264v AC-input Option +10V to 36V DC-input

Power Consumption

Max 40W

Mounting

In-wall / panel mount

Dimension and Weig	ht	
21.5"	H 411 x W 588 x D 79mm (depth 75mm from front wall)	13kg
Slim version	H 406 x W 557 x D 52mm (depth 48mm from front wall)	10kg

Warranty and After Sales Support

Standard 1 year (option for 3 years)

Ordering Information

