Blue Line Fanless FPC-2800

Blue Line Fanless FPC-2800

Model 2

Highlights

Value industrial fanless pc series.

Reduce cost and time spending with our global partner model based on your specific requirements. Let Blue Line take responsibility for delivery on time. Blue Line's ultimate goal is to help our customers get peace of mind by handling all relevant details such as securing the right configuration, software setup, mounting, packaging, labeling etc. Ask for references from your industry.

Blue Line Fanless FPC-2800

- Intel Atom E3845 processor

- Up to 4 x COM, 4 x USB, 2 x GbE

- Compact design

- Fanless operation

- Long product life cycle

- Build-to-order configured to your requirements

Specifications

Model Type

Fanless PC

Form Factor

Compact

Construction

Aluminium

Cooling

Fanless

Environment

Operating temperature	-20°C to +60°C with wide temp. SSD
Humidity	5% to 95% non-condensing

Certification

CE / FCC class A

Processor

Blue Line Fanless FPC-2800

| Model 2 | Intel Atom - Bay Trail E3845, 1.91GHz Quad Core |

Chipset

Integrated SoC

RAM

| Model 2 | 4GB DDR3L |

Storage

| Model 2 | 1 x mSATA SSD |

Front Input / Output

| Model 2 | 2 x USB 2.0, line out, mic in |

Rear Input / Output

| Model 2 | 1 x HDMI, 1 x VGA, 1 x RJ-45 GbE LAN, 1 x USB 2.0, 1 x USB 3.0, 1 x RS232 |

Expansion

| Model 2 | 2 x Mini PCIe slot |

Operating System

Windows 7 / 8 / 10

Windows Embedded 7 / 8

Windows 10 IoT Enterprise

Linux

Power Supply

| Model 2 | +12V DC-in by jack |

Power Consumption

Blue Line Fanless FPC-2800

From 10W to 16W

Dimension and Weight

Model 2	H 35 x W 145 x D 84mm	0.70kg

Mounting

Wall / stand

Accessories Included

AC to DC power adapter

Accessories Optional

Wall mounting kit

Warranty and After Sales Support

Standard 1 year (option for 3 years)

Ordering Information

Model 2	1579-1
Model 1	Faced out - EOL