





Highlights

Blue Line IGPU-3100 is a compact, powerful and advanced GPU solution that offers high performance and can be configured based on individual needs. It is specifically designed for AI and deep learning inference platforms, making it an ideal choice for those in need of efficient and modern computing power. Built for 24/7 operation in various environments.

Reduce cost and time spending with our global partner model based on your specific requirements. Let Blue Line take responsibility for delivery on time. Blue Line's ultimate goal is to help our customers get peace of mind by handling all relevant details such as securing the right configuration, software setup, mounting, packaging, labeling etc. Ask for references from your industry.

IT for Demanding Environments

- Extended product life cycle
- Compact chassis
- 1 x double-slot GPU up to 230W TDP
- 12th generation Intel Core CPU
- Supports Intel VMD
- Supports Windows 10 / 11 / Linux
- · Build-to-order configured to the requirements



Specifications

Model Type	
GPU	
Form Factor	
Compact with front I/O only	
Construction	
Aluminum extrusion heavy duty cold rolled steel	
Cooling	
Fanless with standard configuration	
Option external add-on fan for CPU	
Option internal add-on fan for GPU	
Environment	
Operating temperature	0°C to +60°C w/ 0,7m/s ambient air flow (-20°C to +60°C with wide temp MEM / SSD)
Humidity	10% to 90%, non-condensing
Vibration Endurance	IEC 60068-6-4 (W/SSD: 1Grms STD, random, 5-500 Hz, 1 hr/axis)
Certification	
CE (EN 61000-6-4/EN 61000-6-2), FCC	
Processor	
Intel Core 12th generation i3 / i5 / i7 / i9 (up to 35W TDP))
Chipset	



BLUE LIN E

Intel Q670E

RAM

Up to 64GB, 2 x 262-pin DDR5 SO-DIMM 4800/4000MHz

Storage

2 x 2.5" SSD / HDD drive bays with easy access Supports RAID 0/1

Input / Output

6 x USB 3.2 Gen2x1 (10G) Type A

- 1 x Internal USB 2.0 Type A (Up to 30mm high)
- 1 x 2.5GbE RJ45 Port by Intel i226-V
- 1 x 1GbE RH45 Port by Intel i219-LM with Intel AMT
- 1 x RS-232/422/485 DB9 Port COM1
- 1 x DisplayPort++ with 4096 x 2160 resolution supported
- 1 x HDMI with 4096 x 2160 resolution supported
- 1 x DVI-D with 1920 x 1200 resolution supported
- 1 x 3.5mm jack for Mic-in and Line-out
- 1 x Switch for power on/off with LED (default ATX)
- 1 x 4-pin TB (5.08 mm) for DC input
- 1 x 4-pin TB (5.08 mm) for ignition control, remote power and remote LED

Expansion

1 x Full-size PCI express mini card slot (USB & PCIe interface) w/SIM slot*

L <u>N E</u>

- 1 x M.2 key E 2230 socket
- 1 x M.2 key B 3042/3050/3052/3060 socket w/SIM slot*
- 1 x PCle x 16 gen4
- 1 x PCIe x 4 gen4 (in x8 Slot)
- *Require 4G / 5G module

Management Software

TPM 2.0



Operating System

Windows 10 / 11 Windows 10 IoT Enterprise Linux

Power Supply

+18V to +36V DC-in by 4-Pin terminal block

Power Consumption

TBD

Dimension and Weight

	H 192 x W 170 x D 260mm
Net weight	5.1kg (standard configuration)
Gross weight	6.2kg (standard configuration)

LINE

Mounting

Wall mount

Accessories Included

- 1 x 4-pin terminal block for DC power input
- 1 x 4-pin terminal block for Ignition
- 1 x Extension holder bracket kit

Accessories Optional

Wall mount bracket kit Internal fan module kit External fan module kit Graphics card power cable ATX4P/BTX6 + 2P, L=200mm 500W AC to DC Power adapter, 24V DC EU power core GPS module + antenna kit

> JE IT for Demanding Environments



WIFI/BT module + antenna kit 4G/LTE module + antenna kit

Warranty and After Sales Support

Standard 1 year (option for 3 years)

Ordering Information

1815

