

















# **Highlights**

The Jetson Orin AGX IGPU-1200 is a compact, powerful and configurable GPU solution ideal for deep learning in robots and machine vision. It delivers high performance and is designed for 24/7 operation in diverse environments. With its range of options and configurations, it offers efficient and modern deep-learning inference capabilities.

Reduce cost and time spending with our global partner model based on your specific requirements. Let Blue Line take responsibility for delivery on time. Blue Line's ultimate goal is to help our customers get peace of mind by

handling all relevant details such as securing the right configuration, software setup, mounting, packaging, labeling etc. Ask for references from your industry.

- Fanless AI edge embedded box PC
- Up to12-core Arm Cortex A78AE v8.2 64-bit CPU
- Up to 2048-core Ampere GPU with 64 Tensor Cores
- Up to 64GB onboard memory
- 8 x PoE 30W for camera
- Supports Linux (NVIDIA JetPack 5.1 and above)

## **Specifications**

Humidity

Model Type	
Al box PC	
Form Factor	
Compact	
Construction	
Aluminium	
Cooling	
Fanless	
Environment	

Operating temperature -20°C to 60°C, according to IEC60068-2 with 0.5 m/s

AirFlow

Storage temperature -40°C to 85°C

10% to 90%, non-condensing

Vibration MIL-STD-810G, method 514.7, category 4
Shock MIL-STD-810G, method 516.7, procedure I



<b>^</b>	4	
$\mathbf{C}^{-1}$	rtiti	Cation
$\mathbf{c}$		cation

CE/FCC Class A, according to EN 55032/55035

#### **Processor**

8-core Arm Cortex A78AE v8.2 64-bit CPU 2MB L2 +

4MB L3

NVIDIA Ampere GPU w/1792 Cuda core and 56 Tensor

Cores

Model 2 12-core Arm Cortex A78AE v8.2 64-bit CPU 3MB L2 +

6MB L3

NVIDIA Ampere GPU w/2048 Cuda core and 64 Tensor

Cores

#### Chipset

SoC

#### **RAM**

Model 1 Onboard 32GB 256-bit LPDDR5 204.8 GB/s
Model 2 Onboard 64GB 256-bit LPDDR5 204.8 GB/s

#### **Storage**

2 x 2.5" SATA internal bay

1 x M.2 key-M 2280 for NVMe SSD

1 x SD card slot

#### **Input / Output**

Front I/O 1 x Power switch

1 x reset & recovery switch

1 x SIM card slot\*

1 x SD card slot

1 x audio In/Out

2 x USB 2.0 type-A

1 x Micro USB - OTG function



8 x PoE+ (10/100 MbE, Single-30W/Total-120W)

Rear I/O 5 x SMA connector button\*\*

1 x RS485 via 4-PIN port

2 x RS232 via DB9 port

1 x CAN via DB9 port (isolated)

1 x 10GbE via RJ45 port

1 x 1GbE via RJ45 port

1 x HDMI 2.0 a/b audio

2 x USB 3.0 type-A

8 x GPIO

1 x PWR Input, 3-pin terminal block

\*Internal 4G/LTE module required

\*\* antenna kit required

#### **Expansion**

1 x M.2 key-B 3042/3052 (for 4G/5G module)

1 x M.2 key-M 2230 (for Wi-Fi/BT module)

### **Operating System**

Linux (NVIDIA JetPack 5.0 and above)

#### **Power Supply**

+9 to 55V DC-in by 3-Pin terminal block with ACC function

#### **Power Consumption**

**TBD** 

### **Dimension and Weight**

H 94 x W 242 x D 177mm

Net weight 4.5kg

Gross weight TBD

#### **Mounting**



Wall mount kit

#### **Accessories Included**

1 x power harness cable

2 x alarm I/O cable

1 x RS485 cable

Mounting bracket kit

### **Accessories Optional**

AC to DC Power Adapter, AC100-240V - DC24V, 9.1A, 218.4W

### **Warranty and After Sales Support**

Standard 1 year (option for 3 years)