

















## **Highlights**

Slim, elegant stainless steel HMI for cleanroom. Very easy to clean and disinfect due to smooth sides, rounded edges and a flat, smooth front. Withstands all known cleaning agents and disinfectants.

Cutting-edge touch technology works with gloves improving workflow and productivity. A typical use case would be three layers of gloves, one layer of cotton gloves and two layers of nitrile/latex or silicone gloves. It is also possible to combine with thicker safety gloves. The multi touch display provides auto calibration for seamless operation.

Blue Line's HMIs are designed for 24/7 operation, with a low power consumption, passive cooling and without moving parts for maximum operational reliability.

Available as monitor or with integrated PC, thin client or KVM. Mounting is possible on walls, machines, control cabinets as well as with a large range of supporting arms. Blue Line's modular design makes it possible to configure fully to specific requirements to functionality, finish and environment.

Blue Line's modular design makes it possible to configure to specific needs in functionality, finish and environment. Get free advice from our experts and let us set up a Teams meeting for an online demo and Q&A. Benefit from our experience and knowledge based on numerous installations in biotech and pharmaceutical sites around the world.

- Life Science / GMP / FDA environment
- Stainless steel AISI 304 or 316L
- Easy to clean & disinfect
- Withstands all known detergents: iso-propyl alcohol, non-deionized water, VHP, Spor-Klenz™, Klercide, Actisan, LpH®, Vesphene® and more
- Meets all cleanroom, GMP and FDA requirements
- 21.5" and 24" PCAP multi touch display
- Operable with up to 3 layers of cleanroom gloves
- Full HD resolution 1920 x 1080
- IP65 dust and waterproof
- Integrated PC / client
- Fanless operation
- · Optional Nymi ready integrated reader
- ThinManager support
- Windows 10 / 11 & Linux
- Wide range of options: USB, LAN, serial, reset
- Flexible mounting VESA / wall / pipe / swivel arm / gas arm
- Long product life cycle
- · Customisation according to your requirements



## **Specifications**

**Model Type** 

HMI stainless steel Panel PC

Construction

Fully sealed enclosure in stainless steel AISI 304

Optional acid resistant stainless steel AISI 316L

Cooling

**Fanless** 

**Ingress Protection** 

IP65

**Environment** 

Operating temperature  $0^{\circ}\text{C to } +50^{\circ}\text{C}$ Storage temperature  $-30^{\circ}\text{C to } +70^{\circ}\text{C}$ 

Humidity 10 to 90% @ 40°C, non-condensing

Certification

CE / FCC CLASS A

**Display** 

21.5" 1920 x 1080, 16:9, FHD LCD 24" 1920 x 1080, 16:9, FHD LCD

**Touch** 

Projected capacitive multi touch (supports gloves)



Brightness
300 nits

**Viewing Angle** 

178/178

**Processor** 

Intel Celeron J6412 4C/4T, 2.0GHz (Turbo 2.6GHz)

Intel Core i5 8365UE

Chipset

Integrated SoC

**RAM** 

Celeron J6412 Core i5-8365UE Max 32GB

Max 32GB

**Storage** 

1 x SSD up to 2TB

Front Input / Output

Option for:

**USB** ports

COM ports

Reset

All connectors come with waterproof cap

Nymi ready - integrated reader

Rear Input / Output

1 x Gbe LAN (2 x LAN optional)

1 to 4 x USB ports

COM ports optional

1 x Power input

All connectors come with waterproof cap



#### **Expansion**

WIFI/Bluetooth (optional)

#### **Operating System**

Windows 10 / 11

Windows 10 / 11 IoT Enterprise

Linux

#### **Thin Client**

ThinManager, Microsoft Remote Desktop (RPD), NoTouch OS, VNC, Citrix and others

#### **Power Supply**

+90 to + 264V AC-input

Option +10V to +36V DC-input

#### **Power Consumption**

Max 40W

#### Mounting

**VESA 100** 

Stainless steel supporting arm

Stainless steel tube mount

Stainless steel desktop stand

Other options available according to requirements

#### **Dimension and Weight**

21.5" H 358 x W 567 x D 50mm 12.3kg

24" H 406 x W 639 x D 52mm

#### **Accessories Optional**

Stainless steel scanner bracket

Stainless steel scanner bracket



Antibacterial mouse

Antibacterial keyboard

Combine with Mobile Operator Station

Other options available according to requirements

#### **Warranty and After Sales Support**

Standard 1 year (option for 3 years)

#### **Ordering Information**

1560